Tel: (011) 805-5002 Fax: (011) 805-5033

The AAAMSA Performance Test Certificate

Postal Address: PO Box 7861

Halfway House, 1685



6.86 mm

No Leaks

No Permanent deformation

120N

80N

NOT TRANSFERABLE

Section A: Particulars of A	pplicant		
Applicant:			Certificate
Origin Aluminium	1		Number
P O Box 20971			
DURBAN NORTH			D0722
4016			
Section B: Description of se	ample submitted for testin	ig 🗼	
AAAMSA Class Designation:		Dimensional Sketch of Sample	
A2		600mm 600mm	
Applicants' Drawing Reference:			
ORG. 0	01		
Product			
Alsysco Grec	ian Slider		1200mm
Overall Dimensions:			
1200mm w x 1	200mm h		10
Glass Type:			
Glass Thickness:			1200mm
4mm clear float		Comments by Testing Authority	
Glazing Gaskets:			
4mm Channe	el Gasket		
Weather Seals:			
Woolp	ie		
Hardware:			
Nylon Slider	Handle		
Joint Sealant:			
Silicon	e		
Section C: Testing			
Performance Test	Test Conditions	Measured Result	Allowed Result
Air Infiltration	75 Pa	0,23 {/sec/m²	2.0 l/sec/m²
2. Positive Pressure	1500 Pg	2.90 mm	6.86 mm

Section C: Testing NOT TRANSFERABLE

1500 Pa

300 Pa

2250 Pa

Testing Authority:

Negative Pressure

Water Penetration

Structural Pressure

Operating Forces:

To start movement

To sustain Movement

(Stamp) Test Facility, Durban

R Saunderson PrEng Reg. No. 703219

Date of issue: 26 June 2009

Signed: Mr. R Saunderson

Designation: Testing Officer

Validated by AAAMSA:

2.64 mm

No Leaks

No permanent

deformation

70N

30N

(stamp) AAAMSA PO Box 7861 Halfway House

Date of Validation:

Signed:

Designation: Executive Director