Tel: (011) 805-5002 Fax: (011) 805-5033

Postal Address: PO Box 7861 Halfway House, 1685

## The AAAMSA Performance Test Certificate



## **NOT TRANSFERABLE**

Applicant:	Certificate		
Origin Aluminium	Number		
P O Box 20971			
DURBAN NORTH	D0691		
4016	Book		
Section B: Description of sample submitted for te	esting		
AAAMSA Class Designation:	Dimensional Sketch of Sample		
A1			
Applicants' Drawing Reference:			
AAAMSA 2			
Product			
Vertical Slider	1200mm		
Overall Dimentions:			
900mm w x 1200mm h			
Glass Type:			
Glass Thickness:	900mm		
4mm clear	Comments by Testing Authority		
Glazing Gaskets:			
PVC Channels			
Wheather Seals:			
Fin Pile			
Hardware:			
Fiton Caton	_		
Joint Sealant:			
Silicone			

6	11	-	T 11	
Sec	tion	C:	Testi	na

Performance Test	Test Conditions	Measured Result	Allowed Result
. Air Infiltration	75 Pa	0.19 t/sec/m <sup>2</sup>	2 t/sec/m²
2. Positive Presure	1000 Pa	2.43 mm	5.14 mm
. Negifive Pressure	1000 Pa	2.43 mm	5.14 mm
. Water Penetration	200 Pa	No permanent	No Leaks
Structural Pressure	1500 Pa	deformation	No Permanent deformation
. Operating Forrces:			
To start movement		50N	180N
To sustain Movement		30N	120N

Section D: Certification

Testing Authority:

Test Facility, Durban (Stamp)

R Saunderson PrEng

**Testing Officer** 

Reg. No. 703219

Validated by AAAMSA:

(Stamp) AAAMSA

PO Box 7861 Halfway House

1685

Date of issue: 22 March 2009 Date of Validation: 26 March 2009

signed: Mr. R Saunderson

Designation:

Signed:

Designation: **Executive Director**